

STANDARD UNE/EN 14411:2016

DRY PRESSED CERAMIC TILES WITH WATER ABSORPTION LOWER THAN 0,5%

CERÁMICA PENSADA EN SECO CON ABSORCIÓN MENOR AL 0,5%

Rectified porcelanic

- Reference: **BERA ICE, WHITE (HONED)**
BEREN BISCUIT, BLACK, DARK GREY, GREIGE, LIGHT GREY, SAND (HONED)
- Reference: **BERA ICE, WHITE (NATURAL)**
BEREN BISCUIT, BLACK, DARK GREY, GREIGE, LIGHT GREY, SAND (NATURAL)
- Reference: **BERA ICE, WHITE (SOFT TEXTURED o BH)**
BEREN BISCUIT, BLACK, DARK GREY, GREIGE, LIGHT GREY, SAND (SOFT TEXTURED o BH)
- Reference: **BERA ICE, WHITE (ANTI-SLIP)**
BEREN BISCUIT, BLACK, DARK GREY, GREIGE, LIGHT GREY, SAND (ANTI-SLIP)

Format: ALL SIZES Thickness: 9 mm

Standard Normativas	Features Características	Required Value Valores Requeridos	Value Valor
EN-ISO 10545 / 3	Water absorption / Absorción de agua	Grupo BIa / E ≤ 0,5 %	E ≤ 0,2 %
EN-ISO 10545 / 4	Breaking strength / Resistencia a rotura	≥ 1300 N	≥ 2500 N
EN-ISO 10545 / 4	Bending strength / Resistencia a la flexión	≥ 35 N/mm ²	≥ 52 N/mm ²
EN-ISO 10545 / 6	Resistance to deep abrasion / Resistencia abrasión profunda	≤ 175 mm ³	≤ 139 mm ³ Compliant / Conforme
EN-ISO 10545 / 11	Crazing resistance / Resistencia al cuarteo	Required / Exigida	Compliant / Conforme
EN-ISO 10545 / 12	Frost resistance / Resistencia a la helada	Required / Exigida	Compliant / Conforme
EN-ISO 10545 / 13	Chemical resistance: acids and alkalis / Resistencia química: ácidos y álcalis	Indicated by the manufacturer / Indicado por el fabricante	LA/HA Compliant / Conforme
EN-ISO 10545 / 13	Chemical resistance: domestic cleaning products and swimming pool salts / Resistencia química: productos de limpieza doméstica y sales para piscina	Min. B	A
EN-ISO 10545 / 14	Stain resistance / Resistencia a las manchas	Min. Class 3	Class 5 Natural Class 4 Honed Class 4 Soft Textured - Bush Hammered Class 4 Anti-Slip
EN-ISO 10545 / 2	Surface quality / Calidad de la superficie	Min. 95% of tiles without defect / Min. 95% de los azulejos sin defecto	Compliant / Conforme
EN16165 - ANEXO C	Slip Resistance (Pendulum Test) / Antideslizamiento (Test del péndulo)	Indicated by the manufacturer / Indicado por el fabricante	Class 1 Natural Class 2 Soft Textured Class 2 Bush Hammered/Abujardado Class 3 Anti-Slip
EN16165 - ANEXO B DIN 51130	Critical Angle of Sliding (Inclined Platform) / Ángulo Crítico de Deslizamiento (Plataforma Inclinada)	Indicated by the manufacturer / Indicado por el fabricante	R9 Natural R10 Soft Textured R10 Bush Hammered/Abujardado R11 Antislip
EN16165 - ANEXO A DIN 51097	Critical Angle of Sliding (Wet Areas of Barefoot Walking) / Ángulo Crítico de Deslizamiento (Zonas Húmedas de Andar Descalzo)	Indicated by the manufacturer / Indicado por el fabricante	Class A Natural Class B Soft Textured Class B Bush Hammered/Abujardado Class C Anti-Slip
UNE EN 13501-1:2002	Fire Reaction Test / Test reacción al fuego		A1 / A1FL
VOC	Do not release volatile elements / No desprende elementos volátiles		

LVG Ceramic Surfaces. S.L. reserves the right to make changes and modifications deemed necessary.
LVG Ceramic Surfaces. S.L. se reserva el derecho de hacer variaciones y modificaciones que considere oportunas.

