

TECNICAL INFORMATION

STANDARD UNE/EN 14411:2016

DRY PRESSED CERAMIC TILES WITH WATER ABSORPTION LOWER THAN 0,5%

Rectified porcelanic

Reference: **GUBI CLOUD A/S, LIGHT A/S**

Format:

Thickness: 20 mm

| Standard | Features | Required Value | Value |
|---------------------|---|---|-----------------------------------|
| Normativas | Características | Valores Requeridos | Valor |
| EN-ISO 10545 / 3 | Water absorption / Absorción de agua | Group Bla / E < 0,5 % | E < 0,5 % |
| EN-ISO 10545 / 4 | Breaking strength / Resistencia a rotura | > 1300 N | > 1300 N |
| EN-ISO 10545 / 4 | Bending strength / Resistencia a la flexión | > 35 N/mm ² | > 35 N/mm ² |
| EN-ISO 10545 / 6 | Resistance to deep abrasion / Resistencia abrasión profunda | < 175 mm ³ | Complies with / Cumple |
| EN-ISO 10545 / 11 | Crazing resistance / Resistencia al cuarteo | Required / Exigida | Complies with / Cumple |
| EN-ISO 10545 / 12 | Frost resistance / Resistencia a la helada | Required / Exigida | Complies with / Cumple |
| EN-ISO 10545 / 13 | Chemical resistance: acids and alkalis / Resistencia química: ácidos y álcalis | Indicated by the manufacturer / Indicado por el fabricante | GLA/GHA Complies with / Cumple |
| EN-ISO 10545 / 13 | Chemical resistance: domestic cleaning products and swimming pool salts / Resistencia química: productos de limpieza doméstica y sales para piscina | Min. GB | GA |
| EN-ISO 10545 / 14 | Stain resistance / Resistencia a las manchas | Min. Clase 3 | Clase 5 |
| EN-ISO 10545 / 2 | Surface quality / Calidad de la superficie | Min. 95% of tiles without defect / Min. 95% de los azulejos sin defecto | Guaranteed / Garantizado |
| UNE ENV 12633 | Slip Resistance (Pendulum Test) / Antideslizamiento (Test del péndulo) | Min. Clase 3 | Clase 3 Antislip |
| UNE EN 13501-1:2002 | Fire Reaction Test / Test reacción al fuego | | A1 / A1FL |
| VOC | Do not release volatile elements / No desprende elementos volátiles | | |

QUALITY DEPARTMENT LIVING CERAMICS

STANDARD INTERNATIONAL ISO 9001
QUALITY MANAGEMENT INTERNATIONAL STANDARD OBTAINED IN 2015.



GREEN BUILDING COUNCIL MEMBERSHIP

